K3/K4 PRODUCT DESK REFERENCE

T 800.728.7950 586.294.7950 | **F 800.294.0067** 586.294.0067 | college-park.com

college park

		FOOT	MOUNTING	WEIGHT LIMIT	SIZES	IMPACT	BUILD HEIGHT	WEIGHT**	WTY	L-CODE‡	ENVIROSHELL	HEEL HEIGHT
MICRO-PROCESSOR	NEW! FRESH WATER PROOF	**ODYSSEY iQ**	**Endo (IP)**	**275 lbs**	**23-30 cm**	K3 L M	**3.5 in (23-25 cm) 3.6 in (26-30 cm)**	**1027 g**	**3** *(3 year extended warranty available)*	**L5973** PDAC APPROVED	C T B J standard	0.38 in
TORSION + VERT SHOCK	FRESH WATER PROOF	**VOYAGER**	Endo (IP)	275 lbs (21-25 cm) 330 lbs (26-30 cm)	21-30 cm	K3 K4 M H	7.5 in	1174 g	3	L5987 + L5984 PDAC APPROVED	C T B J standard	0.38 in
VERT SHOCK	FRESH WATER PROOF	**AVIATOR**	Endo (IP)	275 lbs (21-25 cm) 330 lbs (26-30 cm)	21-30 cm	K3 K4 M H	6.5 in	979 g	3	L5987 PDAC APPROVED	C T B J standard	0.38 in
CURVED HYDRAULIC	WATERPROOF	**ODYSSEY$_{K3}$**	Endo (IP)	275 lbs	21-30 cm	K3 L M	3.0 in	749 g	3	L5981 + L5968 PDAC APPROVED	C T B J standard	0.38 in
TRI-AXIAL	 WATERPROOF	**TERRAIN**	Endo (IP)	330 lbs (21-25 cm) 365 lbs (26-30 cm)	21-30 cm	K3 K4 L M H	3.4 in (21-25 cm) 3.6 in (26-30 cm)	815 g	3	L5981 + L5986 PDAC APPROVED	C T B J standard	0.38 in
TRI-AXIAL		**VENTURE**	Endo (IP) Exo (ALX)	250 lbs (21-24 cm) 275 lbs (25-30 cm)*	21-30 cm	K3 K4 L M H	2.5-2.7 in (IP) 5.0-5.2 in (ALX)	585 g	3	L5981 + L5986	C T B J narrow & wide	0.38 in
IST		**VELOCITY**	Endo (IP)	250 lbs (25-26 cm) 275 lbs (27-30 cm)	25-30 cm	K3 K4 L M H	4.7 in (25-26 cm) 5.2 in (27-30 cm)	631 g	3	L5981 + L5986	C T B J narrow & wide	0.38 in
ADJUSTABLE HEEL		**ACCENT**	Endo (IP) D.Pylon (DP)	220 lbs (21-24 cm) 250 lbs (25-28 cm)	21-28 cm	K3 L M	3.3-3.9 in (IP) 7.8-8.0 in (4-H) 7.8-8.1 in (male) 8.3-8.5 in (female)	608 g (IP) 761 g (DP) w/pylon	2	L5981+ L5986+ L5990	C B narrow & wide	2.0 in *(range)*
CARBON+ TORSION	FRESH WATER PROOF	**ORBIT**	Endo (IP)	330 lbs	21-30 cm	K3 K4 L M H	3.7 in (21-25 cm) 3.9 in (26-30 cm)	895 g	3	L5981 + L5984 PDAC APPROVED	C T B J standard	0.38 in
IST	 WATERPROOF	**SOLEUS**	Endo (4-hole)	220 lbs (21-24 cm) 250 lbs (25-26 cm) 275 lbs (27-30 cm)	21-30 cm	K3 K4 M H	6.4 in (21-24 cm) 7.2 in (25-26 cm) 7.6 in (27-30 cm)	667 g	3	L5981 PDAC APPROVED	C T B J narrow & wide	0.38 in
CARBON	 FRESH WATER PROOF	**HORIZON HD**	Endo (IP)	330 lbs (21-25 cm) 365 lbs (26-30 cm)	21-30 cm	K3 K4 L M H	2.3 in	559 g	3	L5981 PDAC APPROVED	C T B J standard	0.38 in
TRI-AXIAL		**TRUSTEP**	Endo (IP) Exo (ALX)	330 lbs (Endo) 352 lbs (Exo)	22-31 cm	K3 K4 L M H	3.5 in (IP) 6.0 in (ALX)	678 g	3	L5979 PDAC APPROVED	C T B J narrow & wide	0.5 in
TRI-AXIAL		**TRIBUTE**	Endo (IP)	220 lbs	21-30 cm	K3 L M	2.4 in	529 g	2	L5979 PDAC APPROVED	C T B J standard narrow & wide	0.38 in
PEDIATRIC	FRESH WATER PROOF	**SCOUT**	Lam Adapter Pyramid Receiver Exo (ALX)	55 lbs (13-15 cm) 100 lbs (16-18 cm) 132 lbs (19-22 cm)	13-22 cm	K3 L M H	1.9-2.1 in (Lam Adpt) 1.8-2.1 in (Pyramid) 2.1-2.4 in (Receiver) 4.1-4.3 in (ALX)	183-360g†	1	L5981 PDAC APPROVED	C T B standard	0.24 in (13-15cm) 0.25 in (16-18 cm) 0.38 in (19-22 cm)
PEDIATRIC		**TRUPER**	Endo (IP) Exo (ALX)	100 lbs (16-18 cm) 132 lbs (19-21 cm)	16-21 cm	K3 L M H	2.1-2.4 in (IP) 4.3-4.6 in (ALX)	215-314 g (16-21 cm)	1	L5979 PDAC APPROVED	C T B standard	0.25 in

* Low impact only

†13-22 cm, including Pyramid Adapter and Enviroshell
**26 cm, including Enviroshell

Caucasian, Tan, Brown, Jet Black

		KNEE	K-LEVEL	WEIGHT LIMIT	WEIGHT	OVERALL HEIGHT	DOME TO KNEE CENTER	FLEXION RANGE	L-CODE†	WTY
MICRO-PROCESSOR	NEW! FRESH WATER PROOF	**ICON**	**K2-K4**	**330 lbs**	**1530 g**	**10.5 in**	**0.67 in**	**130°**	**L5828+ L5845+ L5848+ L5850+ L5856+ L5925** PDAC APPROVED	**3** *(3 year extended warranty available)*
HYDRAULIC	 FRESH WATER PROOF	**CAPITAL**	K3-K4	330 lbs	1010 g (pylon) 1020 g (pyramid)	9.0 in	0.67 in	130°	L5828+ L5845+ L5850+ L5925	3
PNEUMATIC		**VICTOR**	K3	275 lbs	710 g	8.0 in	1.1 in	145°	L5822+ L5845+ L5850	2

‡ The listing of codes with these products should not be construed as a guarantee for coverage or payment. Ultimate responsibility for the coding of services/products rests with the individual practitioner.

K2 PRODUCT DESK REFERENCE

T 800.728.7950 586.294.7950 | **F 800.294.0067** 586.294.0067 | college-park.com

college park

		FOOT	MOUNTING	WEIGHT LIMIT	SIZES	IMPACT	BUILD HEIGHT	WEIGHT**	WTY	L-CODE‡	ENVIROSHELL	HEEL HEIGHT
K2 CURVED HYDRAULIC		**ODYSSEY K2**	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	K2 L	3.1 in (21-24 cm) 3.3 in (25-30 cm	744 g	2	L5972 + L5968	C T B standard	0.38 in
K2	NEW! FRESH WATER PROOF	**TERRAIN iW**	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	K2 L	2.5 in (21-24 cm) 2.7 in (25-26 cm) 2.8 in (27-30 cm)	645 g	2	L5972 + L5986 PDAC APPROVED	C T B standard	0.38 in
		CELSUS	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	K2 L	2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	526 g	2	L5972 + L5986	C T B standard	0.38 in
		TEMPO	Endo (IP)	300 lbs (21-24 cm) 330 lbs (25-30 cm)	21-30 cm	K2 L	2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	500 g	2	L5972 PDAC APPROVED	C T B standard	0.38 in
	WATERPROOF	**BREEZE**	Endo (IP)	220 lbs (21-25 cm) 275 (26-30 cm)	21-30 cm	K2 L	2.4 in (21-25 cm) 2.6 in (26-30 cm)	523 g (25 cm)	2	L5972	C T B standard	0.38 in
K2 VACUUM		**CELSUS iVT**	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	K2 L	2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	652 g	2	L5972 + L5986 + L5781	C T B standard	0.38 in
		TEMPO iVT	Endo (IP)	300 lbs (21-24 cm) 330 lbs (25-30 cm)	21-30 cm	K2 L	2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	626 g	2	L5972 + L5781	C T B standard	0.38 in
STUBBIES	WATERPROOF	**SIDEKICKS**	Endo (IP)	275 lbs	ONE SIZE	K2 L	2.3 in	422 g	2	L5972 + L5986	No Enviroshell	0 in

* Low impact only

** 26 cm, including Enviroshell

Caucasian, Tan, Brown, Jet Black

		KNEE	K-LEVEL	WEIGHT LIMIT	WEIGHT	OVERALL HEIGHT	DOME TO KNEE CENTER	FLEXION RANGE	L-CODE‡	WTY
POLYCENTRIC	NEW! WATERPROOF	**AURA**	K2	300 lbs	665 g	6.32 in	0.65 in	135°	L5611+ L5845+ L5850+ L5925	2
FRICTION BRAKE		**GUARDIAN**	K2	275 lbs	533 g	5.2 in	1.0 in	145°	L5812+ L5845+ L5850+ L5925	2

		LINER	TYPES	PROFILES	SIZES	OVERALL LENGTH	THICKNESSES	L-CODE‡	WTY
TPE GEL	NEW!	**STERLING LINER**	Cushion Locking	Uniform	S, M, M+, L, L+, XL	16.5 in	3 mm, 6 mm, 9 mm	L5679 *(Cushion)* L5673 *(Locking)*	6 months
	NEW!	**STERLING SLEEVE**	Suspension	Uniform	35, 41, 49, 55, 62	16.5 in	5.5 mm at wave	L5685	90 days

‡ The listing of codes with these products should not be construed as a guarantee for coverage or payment. Ultimate responsibility for the coding of services/products rests with the individual practitioner.

ALSO AVAILABLE

CEU COURSES AND EDUCATION

College Park Campus offers free education, training, and certification opportunities for prosthetists and other healthcare professionals.

Enroll today:
www.college-park.com/education

ENDO COMPONENTS

College Park components are highly engineered for noise abatement and strength.

TORSION ADAPTERS

Made of titanium and stainless steel, this adjustable component offers up to 20° of internal and external rotation.

FREE SHIPPING!

Order online to receive free 2-day shipping options! We can directly bill your College Park account.

BE THE FIRST TO KNOW

Sign up for the email newsletter to receive our latest news, events, promotions, and product releases!



LET'S CONNECT

We invite you to follow College Park on social media for helpful resources, inspiring stories, and more.